



Associated Controls (AUST) P/L
Unit A/30-36 Hilly Street,
Mortlake, NSW, 2137
PH: +61 2 8765 9911
Fax: +61 2 8765 9922
WWW: <http://www.ascon.com.au>

PRODUCT ADDENDUM

PRODUCT: P2262, P2282, P2500
DATE: 25TH June 2002

Item: Extra Input Functions

The P2262, P2282, and P2500 Alarm Panels have been updated with new software to provide 2 new input functions. These functions will provide even more versatility for the installer.

Function 1: Input Polarity Selection

An input can now be interpreted by the system with the alarm occurring as a Normally Closed input (Default) or a Normally Open input. This allows for inputs that have different alarm states (ie Closed or Open) to operate on the same panel without the need for specialised software.

Function 2: Ghosted Inputs

An input can now be interpreted by the system as a Ghosted Input. Ghosting allows an input to be connected to the nearest alarm panel without a local alarm occurring on that panel. The input status is transmitted to the network to be acted upon by a remote panel, but the local message for the input is not displayed.

Notes:

With either of these 2 functions the input can still be operated in either Switched or Monitored Mode. The new functions can also be combined in any way to provide a variety of input monitoring.

For more information or clarification, please contact the Associated Controls Sales, Service or Engineering department.